

## 5.2 Guarantee Matrix - Aluminium Substrates

| Environment         |  | Interpon D System                      |  |  |  |
|---------------------|--|--|--|--|--|
|                     |  | Interpon D1036                         |  | Interpon D2525                         |  |
|                     |  | Guarantee Period                       | Requirements <sup>1</sup>                | Guarantee Period                       | Requirements <sup>1</sup>                |
| Normal C3 Inland    |  | 30 years all finishes and gloss levels | Clean every 12 month                     | 40 years all finishes and gloss levels | Clean every 18 months                    |
| Marine - C4 Coastal | 2000m - 5000m from coastline             | 30 years all finishes and gloss levels | Minimum 60 microns Clean every 12 months | 40 years all finishes and gloss levels | Minimum 70 microns Clean every 12 months |
|                     | 500m - 2000m from coastline              | 30 years all finishes and gloss levels | Minimum 60 microns Clean every 6 months  | 40 years all finishes and gloss levels | Minimum 70 microns Clean every 9 months  |
|                     | 50 - 500m from coastline                 | 25 years all finishes and gloss levels | Minimum 60 microns Clean every 3 months  | 30 years all finishes and gloss levels | Minimum 70 microns Clean every 3 months  |
|                     | Less than 50m from coastline             | Not available                          |  | Not available                          |  |
| Industrial – C5-I   | 2000m - 5000m from                       | 30 years                               | Minimum 60 microns                       | 40 years                               | Minimum 70 microns                       |
|                     | source of pollution                      | all finishes and gloss levels          | Clean every 12 months                    | all finishes and gloss levels          | Clean every 12 months                    |
|                     | 500m - 2000m from<br>source of pollution | 30 years all finishes and gloss levels | Minimum 60 microns Clean every 6 months  | 40 years all finishes and gloss levels | Minimum 70 microns Clean every 9 months  |
|                     | 50 - 500m from source<br>of pollution    | 25 years all finishes and gloss levels | Minimum 60 microns Clean every 3 months  | 25 years all finishes and gloss levels | Minimum 70 microns Clean every 3 months  |
|                     | Less than 50m from source of pollution   | Not available                          |  | Not available                          |  |
| Swimming Pools      | Greater than 2m from edge of pool        | 25 years all finishes and gloss levels | Minimum 60 microns                       | 25 years all finishes and gloss levels | Minimum 70 microns                       |
|                     | Less than 2m from edge of pool           | Not available                          | Clean every 3 months                     | Not available                          | Clean every 3 months                     |

Notes: Environmental classification as defined by ISO 12944-2

<sup>&</sup>lt;sup>1</sup> Refer to Interpon D Approved Applicator Manual for full explanation of requirements